WALK BEHIND SCRUBBER DRIER





BATTERIES AND BATTERY CHARGER NOT INCLUDED

INNOVATIONS



ECO SELECT



SERVICE MENU



TELEMATICS GPS



ANTIBACTERIAL PLASTIC



DBL DOUBLE BATTERY LIFE



SLS SELF LEVELING SYSTEM



ANC ADVANCED NOISE CONTRO

CONSUMABLES (CODES AVAILABLE ON PRICE LIST)







PADS



SQUEEZE RUBBER

WALK BEHIND SCRUBBER DRYER





GREEN CLEANING EFFICIENCY



ISO 14067 CARBON FOOTPRINT CERTIFIED



ZERO-COMPROMISE PERFORMANCE

 Delivers industrialgrade results with smooth control



WHISPER-QUIET OPERATION

 Low-noise cleaning for noise-sensitive environments.



COMPACT DESIGN, MAXIMUM REACH

 Maneuvers easily in tight spaces without losing power.

Cordless Freedom with Powerful Performance

Cordless operation with 3–4 hours of runtime for maximum flexibility. Delivers high cleaning efficiency up to 2200 m²/h with a 520 mm scrubbing width. Equipped with 45L clean water and 50L sewage tanks for extended use. Ideal for commercial and industrial spaces needing mobility and performance.

Specifications

NAME	EB-50
Scrubbing Width	520 mm
Squeegee Width	830 mm
Brush Plate Diameter	500 mm
Working Efficiency	0-2200 m²/h
Clean Water Tank	45 L
Sewage Tank	50 L
Brush Motor	24V / 500W
Vacuum Motor	24V / 550W
Cleaning Pump Motor	24V / 120W
Weight	135 kg
Machine Size	1300 × 830 × 1010 mm
Minimum Turning Radius	270 mm

Battery Type



Specification	Lithium Battery	Dry Battery (Lead-Acid / Gel)
Туре	Li-ion / LiFePO4	Lead-Acid / Gel
Voltage	24V / 36V / 48V	24V / 48V
Capacity	100Ah – 400Ah	100Ah – 300Ah
Cycle Life	1500 – 3000 cycles	500 – 1000 cycles
Charging Time	2 – 4 hours	6 – 10 hours
Weight	30-50% lighter	Heavier
Maintenance	Maintenance-free	Occasional (less with Gel)
Discharge Consistency	Stable voltage output	Voltage drop over time
Lifespan	5 – 7 years	2 – 3 years