

## ERS-350



## Specifications

NAME	ERS-350
Model No.	ERS-350
Cleaning Width	1450 mm
Squeegee Width	1350 mm
Side Brush Diameter	500 mm × 2
Main Brush Size	790 × 300 mm
Brush Plate Size	380 mm × 3
Productivity Rate	13050 m <sup>2</sup> /h
Forward Speed	0–9 km/h
Solution Tank	280 L
Recovery Tank	330 L
Dustbin Capacity	60 L
Duration	4-5 H
Vacuuming Filter	4.2 m <sup>2</sup>
Battery Type	Lead-Acid / Lithium
Battery Capacity	72V / 200Ah
Main Brush Motor	72V / 950W
Side Brush Motor	72V / 90W × 2
Dust Vibrating Motor	72V / 120W
Brush Motor	72V / 600W × 3
Suction Motor	72V / 600W × 2
Driving Motor	72V / 2800W
Side Brush Rising Motor	72V / 20W
Brush Plate Rising Motor	72V / 55W
Squeegee Rising Motor	72V / 35W
Vacuuming Motor	72V / 95W
Cleaning Pump	72V/120W
Weight	1320KG
Dimension	2800*1460*1590MM
Minimum Turning Radius	580 MM

### HIGH-PERFORMANCE CLEANING MACHINE FOR INDUSTRIAL & COMMERCIAL USE

Engineered for performance and reliability, this cleaning machine is equipped with durable steel-polyurethane wheels for superior grip, enhanced stability, and safe movement even on inclines. Its dual drain pipe system and high-seal PU tank ensure fast, efficient, and leak-proof drainage—making it an ideal choice for demanding industrial and commercial environments.

